



**Full Featured Outdoor 2MP IR High Speed Dome IP Camera  
With 36x Optical Zoom and Auto Focus HD Megapixel Speed Dome IP Camera**



**Innovative Features**

- ✓ Optical zoom & AF
- ✓ Smart IR LED: efficient infrared array light, low power consumption, the effective radiation distance
- ✓ Starlight low illumination
- ✓ 3D positioning control

Model	<b>AH2911D-36x</b>
Sensor	Sony 2.13Meag Pixel cmos sensor,1/2.8" size
Effective pixels	Full HD (1920*1080)
Frame Rate	25/30/60fps
Lens	36x optical zoom
Focus Length	f4.6 - 165mm
Iris	Fw/1.55 - Ft/5.0
Focus	Auto focus , Manual focus
HFOV	57.6°(w)-2.34°(t)
Minimum illumination	Color: 0. 1Lux F1.55 (30 IRE, 2400 K) B / W: 0Lux at F1.55 (IR LED on)
IR LED	6pcs IR LED with smart IR LED
IR-CUT	Auto day & night dual IR filter switch
IR Distance	150meters
WDR	D-WDR
Video Compression	H.264 and MJPEG simultaneously
Image Setting	Auto AWB/AGC/AE/AIC 3D Noise reduction Adjustable image format, brightness,sharpness, contrast, saturation

	<p>Mirror/Flip</p> <p>Privacy Masks (20 area)</p> <p>Defog</p>
Electronic Shutter	<p>1/5-1/64000second (manual mode);</p> <p>1/5-1/64000second (auto mode)</p>
Audio Encoder	8 kHz, 16 bit encoding, Mono, PCM, G.711
<b>PTZ Information</b>	
Panning Range	360° endless
Tilting Range	-20° ~200°
Preset	256 presets
Preset Cruise	10
<b>General</b>	
Supported Protocols	IPv4/v6, TCP, UDP, DHCP, PPPoE, HTTP, HTTPS, DNS, DDNS, NTP, RTP, RTSP, RTCP, SMTP, FTP, IGMP, ICMP, ARP, Bonjour, UPnP, QoS, SNMP, IEEE 802.1X
Security	IP address filtering, HTTPS encryption, Password protected user level, Anonymous login, IEEE 802.1X network access control
System Integration	ONVIF
Connectors	<p>RJ-45 10Base-T/100Base-TX</p> <p>24V AC power jack</p> <p>4 alarm input and 2 output</p> <p>Line In/out</p> <p>External SD card slot,</p> <p>Support SD/SDHC</p>
Temperature	-40° C ~ 55° C (-40° F ~ 131° F)
Construction	Weatherproof (IP66), Vandal proof metal casing (IK10), Built-in dehumidifier, Scratch-resistant and water-repellent lens glass
Adapter/Power	AC 24V, High PoE
Dimension	(Ø x H): 170mm x 260mm (6.69" x 10.23")