



AH5523T H.265 3MP Outdoor mini IR IP Camera

Features

- 3 Mega Pixels
- 25 / 30 fps in all resolution
- Support H.264+, H.264 and MJPEG
- Fixed lens · IR LED and ICR for day & night
- IP66 weather proof
- PoE : IEEE 802.3af Class3



Camera	
Sensor	Sony 1/2.8" Exmor™ 3.21 MP CMOS sensor
Effective Pixels	2048x1536
Lens	3.6mm fixed lens
Day/Night Mode	<ul style="list-style-type: none"> ● Support Day/Night mode ● Smart Mechanical ICR ● Photo Sensor and Manual mode ● Auto/Manual/Schedule
Minimum Illumination	Color: 0.01 lux @F1.2_(AGC on) B/W: 0.002 lux @F1.2_(AGC on)
IR LED	18 pcs high light LED
IP Module	
Video	
Video Encoder	H.264+, H.264 and MJPEG simultaneously H.264 high profile, main profile 和 baseline
Video Streaming	Two Stream
Frame Rate	25 / 30 fps in all resolutions
Exposure Control	Mode: Auto/Indoor/Manual Exposure (Manual mode: 1/30~1/27,028 seconds) BLC on/off Enhanced WDR

	Max Gain, Auto
Image Settings	AE, AWB 3D noise reduction Color, Brightness, Sharpness, Contrast Image Mirror/Flip Privacy masks .(7setting area) DIS Pixel count Anti-false color AOI/ ROI
On Screen Display	Text, Time and Date overlay Editable OSD
Streaming	Double Streaming UDP, TCP, HTTP, or HTTPS M-JPEG streaming (server push) via HTTP CBR, VBR, EVBR(Enhanced Variable Bitrate)
Network	
Support Protocol	IPv4, IPv6, TCP, UDP, HTTP, HTTPS, SMTP, FTP, NTP, DNS, DDNS, DHCP, DIPS, ARP, Bonjour, UPnP, RTSP, RTP, RTCP, IGMP, PPPoE, 3GPP, Samba, ICMP, SNMP, QoS, CoS, 802.1x, iSCSI
Security	Password protection, IP address filtering, HTTPS encrypted data transmission, User access log
Users	20 Simultaneously unicast users
Ethernet	Auto detect 10M/100M
System Integration	
ONVIF	ONVIF 1.0/ 1.1/ 1.2/ 2.0/ 2.1/ 2.2/ 2.3/ 2.4
Alarm Event	<ul style="list-style-type: none"> ● Upload to FTP or Email ● Upload to NAS via Samba ● Digital out ● Push notifications to App ● Save video or snapshot to mSD card
Alarm Triggers	Motion detection Camera tempering Network disconnect(NFR)
Motion detection	10 motion detection area
General	
PoE	IEEE 802.3af class 3

Certification	CE, FCC, RoHS
Connect	<ul style="list-style-type: none"> • RJ-45 10Base-T/100Base-TX • mSD card
Operation Temperature	-20°C to 50°C
Operation Humidity	20% ~ 80% (non-condensing)
Viewing System	
OS	Windows® 7, 8, 10
Browser	IE 9.0 or later, Firefox 2.0 or later, Safari , Google Chrome
Software	
Search & Install	IP Wizard III
Easy DDNS	DIPS™
Smart phone APP	SecuAngel (Android) and iVanguard (iOS)