

Model: AH65C60

H.265 4K Smart Focus IR IP Camera



特色

- H.265, H.264 , MJPEG tri-encoder
- Motorized lens. Remote zoom and focus. Auto focus and lock focus functions
- Edge-AI inside IP cam: Virtual fence, Person detection, Car detection
- Cyber security: 802.1x, IP filter, HTTPS, RTC (Real-time clock)
- ONVIF Profile S, G, Q, T
- IP67 and IK10 casing

Model	AH65C60
Effective pixels	8MP , 3840*2160
Sensor	Sony Starvis™ sensor, 1/2.8"
Lens Value	f= 2.8-12mm, DC lens
Lens Adjustment	Auto focus, Lock focus, Remote zoom and focus
Min. Illumination	Color: 0.02 lux @F1.2_ B/W: 0.005 lux @F1.2
Day & Night	TDN (Mechanical ICR). Support auto / manual / schedule IR LED on/off
IR LED	Smart IR LED. IR distance up to 30meter

Video Encoder	H.265(HEVC), H.264 and MJPEG simultaneously
Frame Rate	8MP mode: Up to 30fps in all resolutions
Exposure Control	Auto, Manual Exposure Extreme WDR
Image Setting	Auto white balance, Selectable white balance 3D Noise reduction Color, brightness, sharpness, contrast, Hue Image Mirror/Flip, 90° rotation (9:16) Privacy Masks (4 areas) Pixel Count
On Screen Display	Image overlay and multi-language OSD
Streaming	CBR, VBR, EVBR (Enhanced Variable Bitrate) Multi-areas ROI (Region of Interest) AOI (Higher Quality in AOI area)
Audio Encoder	G.711, G.726
Audio Streaming	One-way or two-way
Supported Protocols	IPv4, IPv6, TCP, UDP, HTTP, HTTPS (AES128 or above), SMTP, FTP, NTP, DNS, DDNS, DHCP, DIPS, ARP, Bonjour, UPnP, RTSP, RTP, RTCP, IGMP, PPPoE, 3GPP, Samba, ICMP, SNMP, 802.1x
Security	RTC (Real Time Clock), 802.1x protocol, IP address filtering, HTTPS encrypted data transmission
Users	10 or more simultaneous unicast users
Alarm Triggers	*AI: person detection, car/motorcycle/bus detection, loitering detection, Restricted area detection, Cross line *Multi-areas cell motion detection Camera tampering Audio detection Digital input (DI) Network disconnect (NFR) SD card read/write failure
Alarm Events	File upload via FTP or email File upload via Samba to NAS Notification via email/ HTTP/ and TCP External output activation (DO) Audio alerting

	Save video to mSD card ICR On/Off
Power Supply	DC12V and 802.3af PoE
Connectors	RJ-45 , 10Base-T/100Base-TX/Gigabit LAN 12VDC 1* sensor input (DI) and 1* alarm output (DO) 1* MIC input and 1* audio out mSD card slot Factory default reset button
Operating Temperature	-20°C to 55°C
Certification	IP67 weather proof IK10 vandal proof CE, FCC, RoHS
System Integration	ONVIF Profile S, G, Q, T Open API
OS	Windows® 7, 10 or latter
Browser	IE 9.0 or later, Chrome, Safari
Search & Installation & Backup utility	IP Wizard III

